



All Purpose Primer

DESCRIPTION

GenTite All Purpose Primer is an adhesion promoter designed to clean and prime Rubber Roofing (Black), Rubber Roofing (White), and TPO Roofing (White) membrane prior to application of Peel & Stick accessories.

INSTALLATION

All Purpose Primer is an adhesion promoter that must be used prior to applying any GenTite Peel & Stick accessory to Rubber Roofing (Black), Rubber Roofing (White), or TPO membrane. Refer to current GenTite Application Instructions for additional application instructions.

1. Stir All Purpose Primer thoroughly before and during use. **DO NOT THIN!** A minimum of 2 minutes of vigorous hand mixing with a wooden paint stirrer or its equivalent is required. All sources of ignition should be eliminated; adequate ventilation should exist.
2. Clean all surfaces with a clean cotton rag, removing excess contamination prior to application of the primer.
3. With a scrub pad and handle, apply All Purpose Primer to the roofing membrane using long and continuous back and forth strokes with heavy to moderate pressure along the bonding area until no streaks or puddling occurs.
4. Allow primer to dry until slightly tacky to a dry finger touch.
5. Position the Peel & Stick accessory over the primed area, and remove the release paper, exposing the tape. Apply the accessory to the primed membrane.
6. Using a roller, hand-roll the entire bonding area of the component to ensure adequate adhesion of the component to the primed membrane surface.

PRODUCT DATA

SIZE	CONTENTS	PRODUCT #
1 Gallon (3.8 Liter) Can	4 Cans per Carton	W59GT30089

COVERAGE RATES

- **One-Sided Application:** 200 – 250 ft² per gallon (4.91 – 6.14 m²/L)
- **Two-Sided Application:** 100 – 125 ft² per gallon (2.5 m²/L)
- **3" Seam Tape:** 375' – 450' (114 – 137 m) per gallon
- **6" Cover Tape:** 300' – 375' (91 – 114 m) per gallon

STORAGE

Store indoors in original unopened containers at a temperature between 60 °F to 80 °F (16 °C to 27 °C) for maximum shelf life. Do not store on roof in direct sunlight. When exposed to lower temperatures, restore to room temperature prior to use.



SHELF LIFE

12 months; shelf life will be shortened if exposed to elevated temperatures.

PRECAUTIONARY DATA

This product is extremely flammable. Vapors may cause flash fires. Vapors may ignite explosively under certain conditions. Keep away from fire, sparks, and sources of heat. Extinguish all flames and pilot lights. Turn off electronic motors, stoves, or heaters, or any source of ignition during use and until all vapors have been dispersed. Do not smoke.

- Refer to Safety Data Sheet (SDS) prior to use.
- Open all doors and windows.
- Close containers after use.
- Use with adequate ventilation.
- Avoid prolonged breathing of vapors.
- Avoid prolonged and repeated contact with skin.
- Keep out of reach of children.
- Keep away from eyes.
- Use chemically resistant gloves.

TYPICAL PROPERTIES

PROPERTY	TYPICAL VALUES
Base	Synthetic Polymers
Color	Clear – Translucent Light Yellow
Solids	15 ± 2%
Solvents	Hexane, Naptha
Viscosity	Free Flowing, Easy to Apply
Weight	6.5 ± 0.1 lb/gal (0.8 ± 0.1 kg/L)
Specific Gravity	0.78 ± 0.01
Flash Point	10 °F (-12 °C)

LEED INFORMATION

Recycled Content	
Post-Consumer	0%
Post Industrial	0%